



(19)

JAPANESE PATENT OFFICE

PATENT ABSTRACTS OF JAPAN

(11) Publication number: 62107853 A

(43) Date of publication of application: 19.05.1987

(51) Int. Cl. B22D 17/22
B22D 18/08, B29C 45/26, B29C 45/73
// B29C 33/02

(21) Application number: 60249498
(22) Date of filing: 06.11.1985

(71) Applicant: FUSO LIGHT ALLOYS CO LTD
(72) Inventor: TAKAHASHI KATSUHIKO
SAKAMOTO KATSUMI

(54) TEMPERATURE CONTROL DEVICE FOR METAL MOLD

(57) Abstract

PURPOSE: To improve productivity and to make sure of safety by controlling a temp. of a metal mold, in which coolant in a liq. storage chamber in this inside of a mold is vaporized by heat input from a casting material and then is condensed in a gas condensing part to be flowed back to the chamber.

CONSTITUTION: The coolant with high b.p. 3 such as mercury is stored in the liq. storage chamber 2 in the metal mold 1, in which the gas condensing part 5 is joined to the chamber 2 as closed circuit, and is heated to a settled temp. for the mold 1 by conductive heat from the material 4 poured into a cavity in the mold 1 prevent a temp. drop of the mold 1 under mass production. On the other hand, in case of heating the mold over the settled temp. by the above-mentioned heat input, the coolant 3 is vaporized and cools the

mold 1 to control the mold temp. Further, the vaporized vapor is condensed in the gas condensing part 5 and flowed back again to the chambers 2. A coolant pressure in the chamber 2 is the same or lower than an atmospheric pressure state, and no leakage of the coolant 3, this mold is operated under safety.

COPYRIGHT: (C)1987 JPO&Japio

